

PRODUCT DATA SHEET



measurements [cm]	90° Panorama-Edition			Basis-Edition			Short-Edition	Small-Edition		
	standard	EBH45	EBH60	standard	oven	EBH50	standard	standard	oven	EBH50
execution										
dimensions*	53x53x143	53x53x157	53x53x173	69x52x130	69x52x150	69x52x150	58x48x115	58x48x138	58x48x157	58x48x157
flue pipe Ø	15	15	15	15	15	15	15	15	15	15
rear flue exit**	121,5 ³	135,5 ³	151,5 ³	-	-	125,5 ³	-	116,5	138,5 ³	136,5
external combustion air Ø	10	12,5	10	12,5	12,5	12,5	12,5	12,5	12,5	12,5
weight [kg]	318	345	372	358	386	392	305	342	367	374

technical data

firebox model	SCHLISER ECKMODELL	SCHLISER
supplier	Spiegl Max GmbH&Co.KG	Spiegl Max GmbH&Co.KG
firebox dimensions (wxdxh)	min. 28x28x32cm	min. 33x26x27cm
energy-efficiency-category	A ⁺	A ⁺
heat-power	7,3kW	6,5kW
energy-efficiency-index	115	110
efficiency	84,1%	81,0%
preparations	see instruction manual	see instruction manual
standards	EN-13229, VKF AEAI	EN-13240, VKF AEAI
combustion control	as standard	as standard
15a B-VG	as standard	as standard
BimSchV step 2	as standard	as standard
Austrian eco-label	-	as standard
fuel	firewood	firewood
distance to flammable material	glass panel 90cm, schamotte 8cm	glass panel 90cm, schamotte 8cm
chimney draft	12 (+/- 1) Pa	12 (+/- 2) Pa
flue gas temperature	183°C	214°C
mass flow	6,11 g/s	5,30 g/s
fine dust acc. 13% O ₂	24mg/MJ	13mg/MJ
CO	747mg/MJ	475mg/MJ
OGC	23mg/MJ	30mg/MJ
C _x H _y	36mg/MJ	-
NO _x	84mg/MJ	112mg/MJ

We except aesthetic and technical changes without preannouncement. Errors and misprints excepted!

State of July 2019

¹ max. outer dimensions; can vary up to 5mm

² measured from finished floor level (FF) to flue tube center

³ only with special flue pipe

